P1635 GSM COLINEAR STAINLESS STEEL ELEVATED FEED

PACIFIC

- Covers the range 900 960MHz at less than 2:1 VSWR
- · Ground plane independent
- Rugged, durable antenna suitable for Police, Fire, Ambulance and Emergency Service applications
- · Simple plug and play installation
- Wide choice of installation mounts and brackets
- Interchangeable with P1625 if a smaller, lower gain antenna is needed
- The mounts are terminated with a FastFit jack, which provides a screw-on connection to all common radio communications connectors



FASTFIT JACK

	P1635
Frequency	900 - 960MHz
Antenna Type	Colinear Elevated Feed
Gain	6.5dBi
Typical VSWR	< 1.5:1
Radiation Pattern	Omni - directional
Polarisation	Vertical
Power Rating	100W
Impedance	50 ohms
DC Meter Reading	Open Circuit
Antenna	Stainless Steel
Elevated Feed	316 Stainless Steel
Ferrule & Mount	Glass filled nylon
Mounting Hole Size	16mm
Height / Weight	462mm / 180g
Cable (on P1611/2/8 or P1505 mounts)	5m RG-58AU
Cable (on P1615 or P1508 mounts)	0.5m RG-174
Cable (on P1614 mount)	3m RG-174


MOUNTS FOR P1635







P1611 OR P1615



BRACKETS







P1082B

P1103

P2023






P2024

P2029

VSWR GRAPH



Resolution, 130 Date: 10/11/2004 Model: 83320 ICAL, ON(COAX) Time, 11,42,52 Serial #, 00212033 CW.OFF

18.01.10



P1635

PACIFIC AERIALS

11B Ra Ora Drive East Tamaki 2013 PO Box 38 421 Howick 2145 Auckland New Zealand PHONE: +64-9-253 9450

FAX: +64-9-271 6483

EMAIL: info@pacificaerials.com

WEB: www.pacificaerials.com