Product Announcement



Subject:	New Remote Speaker Microphone and Earpiece Solutions		
	TSM3 Tait Item Code: T03-00045-NDCA TSM3 Description: TP3/TP9 SpkrMic TSM3 IP67 F-bttn-blk 3.5		
Product:	TSM3e Tait Item: T03-00045-NDAA TSM3e Description: TP3/TP9 SpkMic TSM3e IP67 F-bttn-org 3.5		
Date:	January 2021		

Introduction

This is to announce the availability of two new mid-tier professional Remote Speaker Microphones – TSM3, and the TSM3e - which includes enhanced features. The TSM3 and TSM3e are designed to meet the needs and requirements for a wide range of professional users by providing reliable and high quality audio performance.

These new IP67 rated accessories are designed for use with TP3300, TP9300, TP9400, TP9500 and TP9600.


Overview

- Rugged, dust proof and water submersible (IP67 rated with connector jack sealed)
- Tait design water shedding grille and microphone
- Large 360 degree rotating clip
- Push to Talk button
- Function button (programable emergency button)
- Digital and Analog compatible
- 3.5mm connector plug for earpieces
- Recommended earpieces
 - Earpiece In-Ear Acoustic-tube 3.5mm RA-Jack
 0.3-lead (T03-00086-0101)
 - Earpiece Ear-bud C-Hook Black 3.5mm RA-Jack 0.2m-lead (T03-00086-0201)
 - Earpience On-Ear D-Ring Black 3.5mm RA-Jack 0.3m-lead (T03-00086-0301)



Product Overview

- 1. Function button
- 2. Microphone
- 3. Push To Talk (PTT) button
- 4. Speaker
- 5. Connector cable
- 6. 3.5mm audio connector jack
- 7. Rotating dip



Technical information

- Microphone:
 - o Omnidirectional
 - Sensitivity -45d ± 3dB
- Operational temperature: -20°C to 60°C
- Storage temperature: -40°C to 80°C
- Cable pull force: 20kg (5mm cable)

Comparisons and Pricing

Speaker Microphones	Light-weight RSM	NEW TSM3	NEW TSM3e
	T03-00045-ERAA	T03-00045-NDCA	T03-00045-NDAA
Size	Small	Standard	Standard
	Width 50mm	Width 60mm	Width 60mm
Water shedding	No	Yes	Yes
Function	-	F-bttn black	F-bttn orange
Speaker	Impedance 16Ω	Impedance 16Ω	Impedance 8Ω
-	Power Rated 0.5W	Power Rated 1W	Power Rated 2W
Connector	3.5mm	3.5mm	3.5mm
Cable	Diameter – 4mm	Diameter – 4mm	Diameter – 5mm
	Length - 500mm	Length – 360mm	Length – 500mm
	(extends to 1000mm)	(extends to 800mm)	(extends to 1500mm)
Tait Certified	Yes	Yes	Yes
IP Rating	No	IP67 *	IP67 *
Market		Entry level Utility,	Mid-High Utility,
	Business, Transport.	Transport	Transport, Entry level
		Παποροιτ	Public Safety
List Price NZD	\$89	\$125	\$175

* If connector jack is sealed (refer to number 6 on Product Overview diagram)

• Normal discounts apply

Earpieces		Earpiece In-Ear T03-00086-0101	C-Hook T03-00086-0201	D-Ring T03-00086-0301
List Price	NZD	\$45	\$23	\$23

Availability

Available to order now, please contact sales@logicwireless to place your orders.