# P1641 400 - 470MHZ 1/4W FLEXI ELEVATED FEED

- Covers the range 400-470MHz at less than 1.5:1 VSWR
- · Ground plane independent
- · The elevated feed lifts the antenna up above obstructions to a clear all-round view.
- · Rugged, durable antenna suitable for Police, Fire, Ambulance and Emergency Service applications
- · Simple plug and play installation
- · Wide choice of installation mounts and brackets
- Interchangeable with P1631 or P1632 if a higher gain antenna is needed
- · The mounts are terminated with a FastFit jack, which provides a screw-on connection to all common radio communications connectors



JACK	
	P1641
Frequency	400 -470MHz
Antenna Type	Quarterwave Flexi Elevated Feed
Gain	3dBi
Typical VSWR	< 1.5:1
Radiation Pattern	Omni - directional
Polarisation	Vertical
Power Rating	100W
Impedance	50 ohms
DC Meter Reading	Open Circuit
Antenna	Flexi 8mm nylon
Elevated Feed	316 Stainless Steel
Ferrule & Mount	Glass filled nylon
Mounting Hole Size	16mm
Height / Weight	410mm/235g
Cable (on P1611/2/8 mount)	5m RG-58AU
Cable (on P1615 mount)	0.5m RG-174
Cable (on P1614 mount)	3m RG-174

### **MOUNTS FOR P1641**



P1615





P1614 OR P1618

## **BRACKETS**







P1082B

P1103

P2023








P2024

P2028

P2029

# **VSWR GRAPH**



Resolution: 130 Date: 11/11/2004 Model: S332C

ICAL: ON(COAX) Time: 10:05:05 Serial #: 00212033

CW: OFF

9.08.07



PACIFIC



169 Moore Street Howick PO Box 38 421 Howick Auckland New Zealand

**PACIFIC AERIALS** 

**PHONE:** +64-9-5335922 EMAIL: info@pacificaerials.com WEB: www.pacificaerials.com

FAX: +64-9-5335944

FREEFAX NZ: 0800-677688 FREEFAX AUST: 1800-677688